




MANURHIN K'MX 732EVO

Innovative technology




MANURHIN K'MX 732DUO

Aluminium	Brass	Automatic steel	Stainless steel
EN AW 6061	CuZn39Pb3	1.0737	1.4301
44 sec.	46 sec.	59 sec.	104 sec.




MANURHIN K'MX 732DUO

Aluminium	Brass	Automatic steel	Stainless steel
EN AW 6061	CuZn39Pb3	1.0737	1.4301
41 sec.	44 sec.	51 sec.	95 sec.




MANURHIN K'MX 732DUO

Aluminium	Brass	Automatic steel	Stainless steel
EN AW 6061	CuZn39Pb3	1.0737	1.4301
36 sec.	41 sec.	50 sec.	79 sec.




MANURHIN K'MX 732DUO

Aluminium	Brass	Automatic steel	Stainless steel
EN AW 6061	CuZn39Pb3	1.0737	1.4301
31 sec.	32 sec.	35 sec.	49 sec.



MANURHIN K'MX 732DUO

Aluminium	Brass	Automatic steel	Stainless steel
EN AW 6061	CuZn39Pb3	1.0737	1.4301
17 sec.	18 sec.	21 sec.	30 sec.



MANURHIN K'MX 732DUO

Aluminium	Brass	Automatic steel	Stainless steel
EN AW 6061	CuZn39Pb3	1.0737	1.4301
48 sec.	51 sec.	67 sec.	100 sec.

Cycle time is calculated for standard cutting tools, without any special technology, without high pressure coolant and primary with focus on optimal longevity of used cutting tools.